


Draft **ETSI EN 300 220-3-2** V1.1.1 (2016-xx)

**Short Range Devices (SRD) operating
in the frequency range 25 MHz to 1 000 MHz;
Part 3-2: Harmonised Standard covering the essential
requirements of article 3.2 of the Directive 2014/53/EU;
Wireless alarms operating in designated LDC/HR
frequency bands 868,60 MHz to 868,70 MHz,
869,25 MHz to 869,40 MHz, 869,65 MHz to 869,70 MHz**



Draft ETSI EN 300 220-3-2 V1.1.1 (2016-xx)

14

Reference
DEN/ERM-TG28-528

Keywords
harmonised standard, radio, SRD, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword	5
Modal verbs terminology	5
Introduction	5
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references	7
3 Definitions, symbols and abbreviations	8
3.1 Definitions	8
3.2 Symbols	8
3.3 Abbreviations	8
4 Technical requirements specifications	8
4.1 Environmental profile	8
4.2 All equipment conformance requirements	8
4.2.0 Compliance	8
4.2.1 Operating frequency	8
4.2.1.0 Applicability	8
4.2.1.1 Description	9
4.2.1.2 Limits	9
4.2.1.3 Conformance	9
4.2.2 Unwanted emissions in the spurious domain	9
4.2.2.0 Applicability	9
4.2.2.1 Description	9
4.2.2.2 Limits	9
4.2.2.3 Conformance	9
4.3 Transmitters conformance requirements	9
4.3.1 Effective Radiated Power	9
4.3.1.0 Applicability	9
4.3.1.1 Description	9
4.3.1.2 Limits	9
4.3.1.3 Conformance	9
4.3.2 Duty Cycle	9
4.3.2.0 Applicability	9

4.3.2	Duty Cycle	9
4.3.2.0	Applicability	9
4.3.2.1	Description	10
4.3.2.2	Limits	10
4.3.2.3	Conformance	10
4.3.3	Maximum Occupied Bandwidth	10
4.3.3.0	Applicability	10
4.3.3.1	Description	10
4.3.3.2	Limits	10
4.3.3.3	Conformance	10
4.3.4	TX Out Of Band Emissions	10
4.3.4.0	Applicability	10
4.3.4.1	Description	10
4.3.4.2	Limits	10
4.3.4.3	Conformance	10
4.3.5	Transient power	10
4.3.5.0	Applicability	10
4.3.5.1	Description	10
4.3.5.2	Limits	11
4.3.5.3	Conformance	11
4.3.6	Adjacent Channel Power	11
4.3.6.0	Applicability	11
4.3.6.1	Description	11
4.3.6.2	Limits	11
4.3.6.3	Conformance	11
4.3.7	TX behavior under Low Voltage Conditions	11
4.3.7.0	Applicability	11
4.3.7.1	Description	11
4.3.7.2	Limits	11
4.3.7.3	Conformance	11
4.4	Receivers conformance requirements	11
4.4.1	Blocking	11
4.4.1.0	Applicability	11
4.4.1.1	Description	11
4.4.1.2	Limits	12
4.4.1.3	Conformance	12
Annex A (normative): Relationship between the present document and the essential requirements of Directive 2014/53/EU		
		13
Annex B (normative): EU LDC/HR designated frequency bands for wireless alarm equipment		
		14
Annex C (informative): Application form for testing		
		15
C.1	Description	15
C.2	Information as required by ETSI EN 300 220-3-2	15
Annex D (informative): Selection of technical parameters		
		17
D.1	Introduction	17
D.2	Receiver sensitivity	17
D.3	Other receiver parameters	17
Annex E (informative): Change History		
		18
History		19

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.4] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 3-2 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

For non EU countries the present document may be used for regulatory (Type Approval) purposes.

Proposed national transposition dates	
---------------------------------------	--

Date of latest announcement of this EN (doa):	3 months after ETSI publication
---	---------------------------------

Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
--	--------------------

Date of withdrawal of any conflicting National Standard (dow):	18 months after doa
--	---------------------

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part 3-2 of a multi-part deliverable covering wireless alarm Short Range Devices (SRD) operating in the designated LDC/HR frequency range 868,60 MHz to 868,70 MHz, 869,25 MHz to 869,40 MHz, 869,65 MHz to 869,70 MHz.

The present document is structured as follows:

- Clause 2 provides references.
- Clause 3 provides definitions of terms and abbreviations used.
- Clause 4 provides technical requirements.
- Annex A (normative): provides relationship between the present document and essential requirements of Directive 2014/53/EU [i.1].
- Annex B (normative): EU designated frequency bands for wireless alarm equipment.
- Annex C (informative): Application form for testing.
- Annex D (informative): Selection of parameters.

- Annex D (informative): Selection of parameters.
- Annex E (informative): Change History.

1 Scope

The present document applies to LDC/HR wireless alarm equipment types:

- LDC/HR category is defined by the EU Commission Decision 2013/752/EU as:

"The low duty cycle/high reliability device category covers radio devices that rely on low overall spectrum utilisation and low duty cycle spectrum access rules to ensure highly reliable spectrum access and transmissions in shared bands. Typical uses include alarm systems that use radio".

The present document covers equipment intended for fixed, mobile or nomadic use, e.g.:

- stand-alone radio equipment;
- plug-in radio devices intended for use with or within a variety of host systems;
- plug-in radio devices intended for use within combined equipment.

These radio equipment types are capable of operating in the LDC/HR designated frequency bands given in table 1.

Table 1: Wireless alarm LDC/HR designated frequency bands

	Frequency band
Transmit and Receive	868,600 to 868,700 MHz
Transmit and Receive	869,250 to 869,400 MHz
Transmit and Receive	869,650 to 869,700 MHz

The present document contains requirements to demonstrate that radio equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference (article 3.2 of the RE-Directive [i.1]).

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or nonspecific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 220-1 (V3.1.0) (05-2016): " Short Range Devices (SRD) operating in the frequency range 25 MHz to 1 000 MHz; Part 1: Technical characteristics and methods of measurement".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or nonspecific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] Commission Decision 2013/752/EC on harmonization of the radio spectrum for use by short-range devices as amended by subsequent Commission Decisions.
- [i.3] ETSI EG 203 336: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.4] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.5] Commission Decision 2000/299/EC on harmonization of the radio spectrum for use by short-range devices as amended by subsequent Commission Decisions.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the RE-Directive [i.1] and ETSI EN 300 220-1 [1] apply.

3.2 Symbols

For the purposes of the present document, the symbols given in ETSI EN 300 220-1 [1] apply.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI EN 300 220-1 [1] apply.

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile. Normal and extreme tests conditions are defined in ETSI EN 300 220-1 [1], clauses 4.3.3 and 4.3.4.

4.2 All equipment conformance requirements

4.2.0 Compliance

When an operational frequency band is selected from Table B.1 from Annex B for the equipment under test, the equipment shall comply with all parameters, exclusions and notes from the row in Table B.1 unless a different National Radio Interface applies.

4.2.1 Operating frequency

4.2.1.0 Applicability

Clause 4.2.1 applies to all equipment.

4.2.1.1 Description

For the purpose of the present document, the description in ETSI EN 300 220-1 [1], clause 5.1.1 applies.

4.2.1.2 Limits

4.2.1.2 Limits

The provider may declare either one or more operating frequencies and operating channels.

Operating channel(s) shall be entirely within operational frequency bands allowed by Annex B.

4.2.1.3 Conformance

The conformance for this requirement shall be as defined in ETSI EN 300 220-1 [1], clause 5.1.2.

4.2.2 Unwanted emissions in the spurious domain

4.2.2.0 Applicability

Clause 4.2.2 applies to all equipment.

4.2.2.1 Description

For the purpose of the present document, the description in ETSI EN 300 220-1 [1], clauses 5.9.1.1 and 5.9.1.2 apply.

4.2.2.2 Limits

The EUT shall comply with reference limits defined in ETSI EN 300 220-1 [1], clause 5.9.2.

4.2.2.3 Conformance

The conformance tests for this requirement shall be as defined in ETSI EN 300 220-1 [1], clause 5.9.3.

Conformance shall be established under normal test conditions.

4.3 Transmitters conformance requirements

4.3.1 Effective Radiated Power

4.3.1.0 Applicability

Clause 4.3.1 applies to all transmitters.

4.3.1.1 Description

For the purpose of the document, the description in ETSI EN 300 220-1 [1], clause 5.2.1 applies.

4.3.1.2 Limits

The effective radiated power shall not be greater than the value allowed in Table B.1 from Annex B for the chosen operational frequency band(s). The signal shall be located within the operational frequency band.

4.3.1.3 Conformance

The conformance tests for this requirement shall be as defined in ETSI EN 300 220-1 [1], clause 5.2.2.

Conformance shall be established under normal and extreme test conditions.

4.3.2 Duty Cycle

4.3.2.0 Applicability

Clause 4.3.2 applies to all transmitters.

4.3.2.1 Description

For the purpose of the present document, the description in ETSI EN 300 220-1 [1], clause 5.4.1 applies.

4.3.2.2 Limits

The Duty Cycle at the operating frequency shall not be greater than values in annex B for the chosen operational frequency band.

4.3.2.3 Conformance

The conformance for this requirement shall be as defined in ETSI EN 300 220-1 [1], clause 5.4.2.

4.3.2.3 Conformance

The conformance for this requirement shall be as defined in ETSI EN 300 220-1 [1], clause 5.4.2.

4.3.3 Maximum Occupied Bandwidth

4.3.3.0 Applicability

Clause 4.3.3 applies to all transmitters.

4.3.3.1 Description

For the purpose of the present document, the description in ETSI EN 300 220-1 [1], clause 5.6.1 applies.

4.3.3.2 Limits

The EUT shall comply with reference limits defined in ETSI EN 300 220-1 [1], clause 5.6.2.

4.3.3.3 Conformance

The conformance tests for this requirement shall be as defined in ETSI EN 300 220-1 [1], clause 5.6.3.

Conformance shall be established under normal and extreme test conditions.

4.3.4 TX Out Of Band Emissions

4.3.4.0 Applicability

Clause 4.3.5 applies to all transmitters with OCW > 25 kHz.

4.3.4.1 Description

For the purpose of the present document, the description in ETSI EN 300 220-1 [1], clause 5.8.1 applies.

4.3.4.2 Limits

The EUT shall comply with reference limits defined in ETSI EN 300 220-1 [1], clause 5.8.2.

4.3.4.3 Conformance

The conformance tests for this requirement shall be as defined in ETSI EN 300 220-1 [1], clause 5.8.3.

Conformance shall be established under normal and extreme test conditions.

4.3.5 Transient power

4.3.5.0 Applicability

Clause 4.3.5 applies to all transmitters.

4.3.5.1 Description

For the purpose of the present document, the description in ETSI EN 300 220-1 [1], clause 5.10.1 applies.

4.3.5.2 Limits

The EUT shall comply with reference limits defined in ETSI EN 300 220-1 [1], clause 5.10.2 under normal test condition.

4.3.5.3 Conformance

The conformance tests for this requirement shall be as defined in ETSI EN 300 220-1 [1], clause 5.10.3.

Conformance shall be established under normal test conditions.

4.3.6 Adjacent Channel Power

4.3.6.0 Applicability

Clause 4.3.6 applies to all transmitters with OCW \leq 25 kHz.

4.3.6.1 Description

For the purpose of the present document, the description in ETSI EN 300 220-1 [1], clause 5.11.1 applies.

4.3.6.2 Limits

For the purpose of the present document, the description in ETSI EN 300 220-1 [1], clause 5.11.1 applies.

4.3.6.2 Limits

Where the Operating Channel is less than or equal to 25 kHz, the power in the adjacent channels shall not exceed the reference limits defined in ETSI EN 300 220-1 [1], clause 5.11.2.

4.3.6.3 Conformance

The conformance tests for this requirement shall be as defined in ETSI EN 300 220-1 [1], clause 5.11.3.

Conformance shall be established under normal and extreme test conditions.

4.3.7 TX behavior under Low Voltage Conditions

4.3.7.0 Applicability

Clause 4.3.7 applies to battery powered transmitters.

4.3.7.1 Description

For the purpose of the present document, the description in ETSI EN 300 220-1 [1], clause 5.12.1 applies.

4.3.7.2 Limits

The EUT shall comply with reference limits defined in ETSI EN 300 220-1 [1], clause 5.12.2.

4.3.7.3 Conformance

The conformance tests for this requirement shall be as defined in ETSI EN 300 220-1 [1], clause 5.12.3.

Conformance shall be established under normal test conditions.

4.4 Receivers conformance requirements

4.4.1 Blocking

4.4.1.0 Applicability

Clause 4.4.1 applies to all receivers.

4.4.1.1 Description

For the purpose of the present document, the description in ETSI EN 300 220-1 [1], clause 5.18.1 applies.

4.4.1.2 Limits

The blocking level shall be better or equal to category 2 reference limits level defined in ETSI EN 300 220-1 [1], clause 5.18.3.

4.4.1.3 Conformance

The conformance tests for this requirement shall be as defined in ETSI EN 300 220-1 [1], clause 5.18.6.

Conformance shall be established under normal test conditions.

Annex A (normative):

Relationship between the present document and the essential requirements of Directive 2014/53/EU

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.4] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

Table A.1: Relationship between the present document and the essential requirements of Directive 2014/53/EU

Harmonised Standard ETSI EN 300 220-3-2				
The following requirements are relevant to the presumption of conformity under the article 3.2 of Directive 2014/53/EU [i.1]				
Requirement			Requirement Conditionality	
No	Description	Reference: Clause No	U/C	Condition
1	Operating frequency	4.2.1	U	
2	Unwanted emissions in the spurious domain	4.3.6	U	
3	TX Transmitter effective radiated power	4.3.1	U	
5	TX Duty cycle	4.3.2	U	
6	TX Occupied bandwidth	4.3.3	U	
7	TX out of band emissions	4.3.4	C	Applies to EUT with OCW > 25 kHz
8	TX Transient	4.3.5	U	
9	TX Adjacent channel power	4.3.6	C	Applies to EUT with OCW ≤ 25 kHz
10	TX behaviour under low voltage conditions	4.3.7	C	Applies to battery powered EUT
17	RX Blocking	4.4.1	U	

Key to columns:

Requirement:

No A unique identifier for one row of the table which may be used to identify a requirement.

Description A textual reference to the requirement.

Clause Number Identification of clause(s) defining the requirement in the present document unless another document is referenced explicitly.

Requirement Conditionality:

U/C Indicates whether the requirement shall be unconditionally applicable (U) or is conditional upon the manufacturers claimed functionality of the equipment (C).

Condition Explains the conditions when the requirement shall or shall not be applicable for a requirement which is classified "conditional".

Presumption of conformity stays valid only as long as a reference to the present document is maintained in the list published in the Official Journal of the European Union. Users of the present document should consult frequently the latest list published in the Official Journal of the European Union.

Other Union legislation may be applicable to the product(s) falling within the scope of the present document.

ETSI

Draft ETSI EN 300 220-3-2 V1.1.1 (2016-xx)

14

Annex B (normative):

EU LDC/HR designated frequency bands for wireless alarm equipment

According to Article 8 (2) of Directive 2014/53/EU [i.1], the European Commission has adopted implementing acts establishing the equivalence between notified national radio interfaces and assigning a radio equipment class. So called Class 1 equipment is equipment that can be placed on the market and be put into service without restrictions. The Commission, in consultation with Member States, publishes an

implementing acts establishing the equivalence between notified national radio interfaces and assigning a radio equipment class. So called Class 1 equipment is equipment that can be placed on the market and be put into service without restrictions. The Commission, in consultation with Member States, publishes an indicative and non-exhaustive list of equipment falling within the scope of Class 1. Table B.1 summarizes the relevant parameters in the band 25 MHz to 1 000 MHz from the latest list of class 1 equipment (December 2014). This table is in line with the harmonised frequency bands and technical parameters for short-range devices from EC Decision 2013/752/EU [i.2].

Table B.1: EU LDC/HR designated frequency bands for wireless alarm

	Frequency Band	Maximum radiated power, e.r.p.	Channel access and occupation rules	OCW	Band number from EC Decision 2013/752/ EU [i.2]	Class 1 sub-class number according Commission Decision 2000/299/EU [i.5]
A	868,600 MHz to 868,700 MHz	10 mW e.r.p.	≤ 1 % duty cycle	100 kHz or 25 kHz	49	32
B	869,250 MHz to 869,300 MHz	10 mW e.r.p.	≤ 0,1 % duty cycle	25 kHz	52	33
C	869,300 MHz to 869,400 MHz	10 mW e.r.p.	≤ 1 % duty cycle	25 kHz	53	72
D	869,650 MHz to 869,700 MHz	25 mW e.r.p.	≤ 10 % duty cycle	25 kHz	55	34

ETSI

Draft ETSI EN 300 220-3-2 V1.1.1 (2016-xx)
19

Annex C (informative): Application form for testing

C.1 Description

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the application form in this annex so that it can be used for its intended purposes and may further publish the completed application form.

The form contained in this annex may be used by the supplier to comply with the requirement contained in clause 4 to provide the necessary information about the equipment to the test laboratory prior to the testing. It contains product information as well as other information which might be required to define which configurations are to be tested, which tests are to be performed as well the test conditions.

This application form should form an integral part of the test report.

C.2 Information as required by ETSI EN 300 220-3-2

In accordance with ETSI EN 300 220-3-2, clause 4, the following information is provided by the supplier:

a) **The name of the manufacturer or his trademark:**

.....

b) **The type equipment designation:**

.....

c) **The Application(s) of the equipment:**

.....

.....

d) **The operating frequency(ies):**

.....

.....

e) **The operational frequency band(s):**

.....

- e) **The operational frequency band(s):**

- f) **The operating channel(s) width(s):**

 The operating channel is less than or equal to 25 kHz ?
- g) **Maximum radio-frequency power transmitted in the frequency band in which the radio equipment operates:**

- h) **What is the spectrum access mechanism of the equipment?**
 Duty cycle
- i) **Is the equipment battery powered?**
 Yes No
- j) **Is the equipment frequency agile?**
 Yes No

Annex D (informative): Selection of technical parameters

D.1 Introduction

ETSI EG 203 336 [i.3] lists candidate technical parameters to be included in a Harmonised Standard aimed at providing a presumption of conformity of radio equipment with the essential requirements in articles 3.1(b) and 3.2 of the Radio Equipment Directive 2014/53/EU [i.1].

Essential requirements are high level objectives described in European Directives. The purpose of the Harmonised Standard is to translate those high level objectives into detailed technical specifications.

This annex provides information regarding selected parameters that may be in or not in the present document.

D.2 Receiver sensitivity

Receiver sensitivity is not specified in the present document in order to allow providers the freedom to tailor equipment to specific circumstances.

For instance, equipment covered by the present document may have to operate in the presence of elevated background electromagnetic noise or in proximity to other transmitters. In such circumstances, specifying a high level of sensitivity may be counter productive to the aim of achieving reliable communications.

Providers should be aware of the situations in which equipment is likely to be used. In particular, it should be noted that frequency bands covered in the present document may be adjacent to bands used by 500 mW SRDs. Other equipment operating in adjacent bands may have out of band emissions falling into bands covered by the present document. In such cases there is a possibility of in-band interference that may affect operation.

D.3 Other receiver parameters

Because sensitivity is not specified, it follows that co-channel rejection is not specified.

Adjacent channel selectivity is not specified in the present document because only applicable to category 1 receivers.

Receiver saturation is not specified in the present document because only applicable to category 1 receivers.

Spurious response rejection is not specified in the present document because only applicable to category 1 receivers.

Spurious response rejection is not specified in the present document because only applicable to category 1 receivers.

Many receiver requirements fall under the general heading of linearity and these are covered in the present document by requirements on blocking performance.

Intermodulation performance is not specified in order to simplify testing. The risk of failure due to second order intermodulation products is considered low because the blocking specification leads to the ability to handle strong out of band signals. Manufacturers should assess the risk of intermodulation products when operating adjacent to high occupancy bands.

Annex E (informative): Change History

Date	Version	Information about changes
February 2016	1.1.1	First publication of the EN after approval by TC ERM at ERM#58 (22 February - 26 February 2016; Sophia Antipolis)

History

Document history		
V1.1.0	May 2016	EN Approval Procedure AP 20160801: 2016-05-03 to 2016-08-01
V1.1.1	September 2016	Draft for TC ERM approval after PE comments resolution